



- COMPRESSOR:
1. CYLINDER: 3x $\phi 49 \times 40$;
 2. DISPLACEMENT: 226.3cc;
 3. WEIGHT: 10.6kg;
 4. OPERATING SPEED: 4200rpm(Max5000rpm);
 5. DIRECTION OF ROTATION: CLOCK WISE;
 6. LEAKAGE TEST: ADDITIONAL TABLE

ITEM	HIGH PRESSURE SIDE	LOW PRESSURE SIDE
AIRPROOF PRESSURE	2.9 (30)	1.5 (15)
RESISTANT PRESSURE	4.4 (45)	2.2 (22.5)

7. GAS LEAK: < 30g/year

- MAGNETIC CLUTCH:
1. RATED VOLTAGE: DC 24V;
 2. SHAPE OF THE BELT: PV7;
 3. STATIC TORSION: ABOVE 68.6N.m;
 4. WATTAGE: 47W;
 5. WEIGHT: 4kg.

- NOTE FOR COMPRESSOR INSTALLATION:
1. INCLINATION AT INSTALLATION SHOULD BE < 15° IN LATERAL DIRECTION; < 5° FOR FRONT LIFTING; AND NO LIFTING FOR REAR SIDE;
 2. DURING TRANSPORTATION, COMPRESSOR SHOULD NOT BE INCLINED BY 45° IN BOTH LATERAL AND LONGITUDINAL DIRECTIONS; BEFORE INSTALLATION, COMPRESSOR SHOULD BE PLACED HORIZONTALLY FOR MORE THAN 10 MINUTES;
 3. REQUIREMENTS FOR THE BOLT TORSIONS:
FIXED BRACKET BOLT: 16-50N.m
FIXED LINKER BOLT: 20-24N.m

				HCP-23		HZL	
图号	规格	分号	更改日期	更改人	日期	COMP ASSEMBLY	
设计	审核	2004.12.28	标准化			比例	
审核						1:1	
工艺						305160-3600	